

## Vlastnosti

top



- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Hladký p?ední panel lze p?izp?sobit logogramy, osv?tlením, nápisy ?i bezpečnostními a informa?ními signály, dle požadavk? zákazníka.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Jiné barvy jsou dostupné na vyžádání.
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Jiné barvy jsou dostupné na vyžádání.
- Výstupní lopatky z eloxovaného hliníku s profilem ve tvaru k?ídla.
- Zakroucené ventilátory s p?í?ným proud?ním a nízkou hlu?ností, pohán?né 2rychlostním motorem s vn?jším rotorem.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. Typ "E" s elektrickými stín?nými sou?ástkami, t?emi úrovn?mi s integrovanou regulací. Typ "A" bez oh?evu, pouze vzduch.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

## Specifikace

50Hz

## Neoh?ívaná

Model	(m <sup>3</sup> /h)	(m)
TOP 1000 A	3.5	
TOP 1500 A	3.5	
TOP 2000 A	3.5	

## Elektrický oh?ev

Model	(m <sup>3</sup> /h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

## Oh?ev vodou

Model	(m <sup>3</sup> /h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

Rozm?ry

